(012) 326 7771
(012) 326 3200 (Fax)

BioClin Solutions ™

FURN-506

E500X 4 SECTION ELECTRIC HOSPITAL BED

** Mattress for the bed is optional*

The new Enterprise® 5000 curved mattress deck bed is the latest general use hospital electrical bed with 4-Section Hi-Lo, Trendellenberg and built-in battery back-up. It is easy and intuitive to use.
It has a **1 YEAR WARRANTY**

Key Features

30 Degree Backrest Angle

The backrest will pause when raised to an angle of 30 degrees, ensuring easy and positive back-rest adjustment time after time.



Underbed Lights

Lighting fitted under both sides of the bed helps to improve patient safety and security, by illuminating the bed exit area.

Attendant Control Panel

One-Button-Push control panel with updated graphics and layout for intuitive ease of use. Features auto-CPR, lock-outs and cardiac chair position.

PICTURES ARE FOR ILLUSTRATIVE PURPOSES ONLY AND MAY VARY FROM ACTUAL PRODUCT. E&OE

sales@bioclin.co.za
www.bioclin.co.za
Unit 4, 490 Barolong Street,
Icon Industrial Park,Sunderland Ridge,
Centurion, 0157

BioClin Solutions ™

Low Height
An exceptional low height of 320mm is achieved via One-Button-Push.

Curved Mattress Deck
The patented Bio-Contour profiling system blends a unique combination of bed movements with a curved mattress deck.

Ease of Access
The open allows ease of access to help improve decontamination procedures. Deck sheets are lightweight, smooth and easily removed.er flexibility and choice.

PRODUCT SPECIFICATIONS

FEATURE	
Electrically operated backrest, knee-break and height adjustment	
Electrically operated Trendelenberg / Reverse Trendelenberg tilt	±12°
Auto-CPR and Auto-contour button	
Battery back-up	
Bio-Contour profiling system	
One button chair position	
Dual sided CPR levers	
30° backrest angle pause	
Angle indicators for backrest	
Built-in bed extension with mattress platform extension	
Removable head and foot panels with choice of colour infills	
Drainage bag rails	
Removable plastic deck sheets	
Linked braking / steering system with four braking castors	
125mm single wheel castors	
Full width brake bar (foot end only)	
DIN rails	
Under-bed light	
Folding safety sides	
Pull-out linen shelf	

SPECIFICATIONS	
Overall standard length	2300mm
Overall width	1030mm
Mattress length standard	1980x860x150mm
Safety standard	IEC60601-2-52
Backrest length	850mm
Seat length	215mm
Calf length	560mm
Thigh length	365mm
Safe working load/Maximum patient weight	250kg/185kg
Head down tilt	12°
Foot down tilt	12°
Backrest angle	62°
Backrest pause	30°
Thigh angle	20°
Calf angle	16°
Ingress protection	IPX4
Shock protection	Class 1, Type B
Power in	1.25A at 230V AC 50 / 60Hz
Power in	2A at 120V AC 50 / 60Hz